

Presenting

AxRUST4™

The Rust Warrior

AxRUST4™ is an EXCELLENT MRO (Maintenance Repair Overhaul) product in its unmatched Quality, Reliability and Adaptability for numerous industrial, automotive, and domestic applications

- CLEANS metal surface & REMOVES rust even penetrating into most greases, dirt and contamination
- LOOSENS tight assembly parts such as rusted bolts/nuts, fasteners, joints etc. by penetrating into the most intricate microscopic areas and irregularities etc.
- LUBRICATES pivoted joints, hinges, chains etc. to eliminate noise and improve operations
- DISPLACES moisture from metal surfaces
- INHIBITS RUST after cleaning, loosening and lubrication (needs to be re-applied on the affected areas)

- CLEANS
- LUBRICATES
- LOOSENS TIGHT ASSEMBLIES
- DISPLACES MOISTURE
- INHIBITS RUST

The Rust Warrior

AxRUST4™

SPECIAL FEATURES

- CO₂ propellant
- CFC Free
- Multiple degrees of freedom while spraying

CLEANS
LUBRICATES & LOOSENS
DISPLACES MOISTURE
INHIBITS RUST

Zerust®
Corrosion Solutions



Zerust®
Corrosion Solutions



Applications

Automotive



Domestic



Industrial and Heavy machinery



Disclaimer: We cannot anticipate or control the many conditions under which the information and the product may be used. Hence, we make no warranty, express or implied, as to the effects of use (including but not limited to damage or injury) or the results to be obtained, whether or not used in accordance with the directions. The information furnished is believed to be accurate to the best of our knowledge. Harita-NTI is not liable for any loss, damage, incidental or consequential. Buyer assumes all responsibility in use, storage and handling of this product.

AXRUST 4™

CLEANS AND INHIBITS RUST

LUBRICATES, LOOSENS AND DISPLACES MOISTURE

Rusted




After using AxRUST 4™



Loosens nuts & bolts



Lubricates



Cleans : Cleans the metal surface from rust, grease, dirt and contamination.

Loosens & Lubricates : Penetrates the metal parts to lubricate and loosen tight assemblies such as nuts, bolts, knobs, hinges, bearings, automobile and domestic fixtures etc.

Displaces moisture : Displaces moisture on the metal surface.

Inhibits rust : Protects metals such as engine parts, automobile under hood parts, antiques, bicycle parts, tool kits, household metal objects, cables etc. Can be used for protection of Ferrous, Aluminium, Copper, Brass, Bronze and other multi-metal parts / assemblies.

Physical Characteristics

Appearance Form	Pale Yellow Liquid
Odor	Solvent odor with proprietary fragrance
Flash point in °C	> 42
Density @ 15 °C	0.78 - 0.79
Pour point in °C	Below - 13
Flammability	Yes
Explosion hazard	This product is flammable and may be ignited by heat or flame
Shelf Life	2 Years

Directions

- 1) Shake well prior to use.
- 2) Hold the can 4-6" away.
- 3) Spray the parts to be treated and allow sufficient time for the product to penetrate and soak.
 - a. For rust removal, use a cloth/scotch brite as required to remove rust
 - b. For Loosening of tight assemblies, use a spanner and unscrew the subject part
- 4) If corrosion protection is required, reapply the product or do not wipe off.
- 5) Use extender tube for pin point application. Replace the cap after use.

Keep away from direct sun light. Do not use on flammable & easily explosive components /premises / hot surfaces.

Available sizes in Aerosol cans: 125ml, 250ml, 500ml.

Please contact the local distributor or the customer service representative for any queries / comments. User manual available upon request from a local distributor.

CAUTIONS:

Inflammable. Keep Storage away from children, direct sunlight, heat, sparks, open flame, cigarettes & ignition. Disconnect electrical contacts before applying. Do not induce vomiting if swallowed. Inhalation is harmful. Use with adequate ventilation. Avoid skin / eye contact & breathing vapors. Personal protective equipment (PPE) recommended during application. Do not puncture or incinerate. Do not discard in trash compactor. Do not expose containers to temperatures above 45°C.



Manufactured by

Harita-NTI Limited

A3, Ambattur Industrial Estate, Chennai – 600 058, Tamilnadu, Ph: 044 - 2635 7087

Website : www.haritanti.com, Email : enquiry@scl.co.in

Disclaimer: We cannot anticipate or control the many conditions under which the information and the product may be used. Hence, we make no warranty, express or implied, as to the effects of use (including but not limited to damage or injury) or the results to be obtained, whether or not used in accordance with the directions. The information furnished is believed to be accurate to the best of our knowledge. Harita-NTI is not liable for any loss, damage, incidental or consequential. Buyer assumes all responsibility in use, storage and handling of this product.