

**ZERUST® - EXCOR® VCI**

## Zerust® Non-Ferrous Film

Zerust®/Excor® VCI Non-ferrous Film provides cost-effective and versatile protection against corrosion damage for non-ferrous metals such as aluminum, copper, brass, bronze and galvanized steel in shipping and storage.

Zerust VCI packaging film diffuses proprietary Zerust VCIs (Vapor Corrosion Inhibitors) to protect metals for years. Use Zerust VCI Non-ferrous Film to protect metal components and assemblies and more from corrosion. For additional protection and use in challenging environments, packaging can be used with Zerust corrosion inhibitor liquid RPs and VCI diffuser products. Check with your Zerust/Excor representative for a comprehensive corrosion management solution most effective for your metal assets.

Zerust is the inventor of poly VCI technology and Zerust VCI film has proven its performance and safety\* with thousands of customers worldwide for over 35 years. It is used to protect valuable metal items for manufacturers in industries such as automotive, agricultural, aerospace and mining. Zerust/Excor offers onsite support and service using our local partners in more than 60 countries.

### Application Example

A Zerust VCI Non-ferrous Film Bag protect a copper coil from corrosion during shipping and storage.



### Benefits

Effective corrosion protection and packaging combined in one step

Metals are ready for use and assembly directly out of the packaging

Available with ESD protection

Provides safe\* and effective Zerust VCI protection.

Recyclable

### Application Type

Storage  
Shipping  
Work in progress

\*Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHIMS regulations.

## Specifications



<b>Product Information</b>	Zerust®/Excor® Non-ferrous Film is a polyethylene product impregnated with vapor corrosion inhibitors.
<b>Protected Metal Types</b>	Protects non-ferrous metals such as aluminum, copper, brass, bronze, and galvanized.
<b>Protection Life</b>	Protects clean metals for years when used correctly and utilized within three years from receipt.
<b>Storage</b>	Store in original packaging away from direct sunlight in conditions below 85°F (30°C) and 50% RH until ready for use.

## Availability

Zerust Non-ferrous VCI Film is available upon request. Contact Harita-NTI account manager for pricing and availability.

Property	Direction (Machine or Transverse)	Zerust Non-ferrous Film*	ASTM Test Method
Film Thickness	-	3.9mil (100 µm)	D-6988
Dart Impact Resistance	-	230 g	D-1709
Tensile Strength at Yield	MD	260 kg/sq.cm (25.5 MPa)	D-882
	TD	250 kg/sq.cm (24.5 MPa)	
Tensile Strength at Break	MD	250 kg/sq.cm (24.5 MPa)	D-882
	TD	240 kg/sq.cm (23.5 MPa)	
Elongation at Break	MD	820%	D-882
	TD	910%	
Vapor Inhibiting Ability (VIA)	-	Pass	NACE TM0208-2013

\* Typical values, not meant to be a specification.

## Recyclable

Dispose of in accordance with local, national and international regulations. Check on options for recycling and incineration.

## Safety

- Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHIMS regulations.
- Zerust VCI chemistry is safe for sensitive electronics. No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

Warranty and Disclaimer Information: We guarantee our products conform to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied as to the effects of use (including, but not limited to, damage or injury). For full warranty and disclaimer information visit, [www.zerust.com/warranty](http://www.zerust.com/warranty).

©2015 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: ActivPak®, Cor-Tab®, EXCOR®, Flange Saver®, ICT®, NTI®, Plastabs®, Z-CIS®, Zerion®, ZERUST®, The ZERUST People®, and the Color "Yellow". ABRIGO®, UNICO®, and VALENO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC.

## Contact Us

**ZERUST® EXCOR®**

A product of:  
Northern Technologies International Corp



**Harita-NTI Limited**  
A3, First Main Road,  
Ambattur Industrial estate,  
Ambattur, Chennai-600058.

Phone. +91-44-26357087  
Fax. +91-44-26357088  
[salesadmin@scl.co.in](mailto:salesadmin@scl.co.in)  
[www.haritanti.com](http://www.haritanti.com)