



# Harkool ME

## Product Datasheet

### Description

HARKOOL – ME is high-performing, mild emulsion coolant designed for multiple operations of general machining of cast iron, steel and aluminum alloys. It reduces coolant consumption by less drag out, provides pro long system life and meet your machining needs when working with a wide range of materials.


### Typical Characteristics

Properties	Results	Method
Appearance	Clear Amber Liquid	Visual
Density @ 29.5°C, g/mL	0.893, typical	ASTM D 1298
pH of 5% in DI Water	9.2	ASTM E70
Viscosity at 40°C, cSt	48 to 55	ASTM D 445
Flashpoint COC, °C	160	ASTM D 56

### Benefits

- This product is free from heavy metals, boron, secondary amine, and nitrosamine
- Low foam in recommended water conditions
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Lubrication package specifically designed to enhance tool life and improve surface finish in components.
- Multimetal compatible product.

**Disclaimer:** We cannot anticipate or control the many conditions under which the information and the product may be used. Hence, we make no warranty, express or implied, as to the effects of use (including but not limited to damage or injury) or the results to be obtained, whether or not used in accordance with the directions. The information furnished is believed to be accurate to the best of our knowledge. Harita-NTI is not liable for any loss, damage, incidental or consequential. Buyer assumes all responsibility in use, storage and handling of this product.



HNTI Limited

## Harkool ME

---

### Operating Conditions

Temperature	Ambient
Concentration	5 to 15%*
pH @ 29.5°C	8.5 to 9.2
Water TDS	0- 500 ppm

### Application:

Harkool ME is suitable for all kind of general machining operations like turning, drilling, and milling. It is also Compatible with both ferrous and Non-Ferrous Metals.

### Solubility

When mixed with water, they form a milky emulsion that is an excellent choice for general purpose machining.

### Storage

Store in (34 to 122°F / 1 to 50°C), dry place and away from sunlight in original packaging for up to 6 months from the date of manufacture.

Safety & Warning: Review Material Safety Data Sheet for appropriate health and safety warnings before use.

Spillage : Flush with water. Clean and dispose of in accordance with federal, state, or local regulations.

**Disclaimer:** We cannot anticipate or control the many conditions under which the information and the product may be used. Hence, we make no warranty, express or implied, as to the effects of use (including but not limited to damage or injury) or the results to be obtained, whether or not used in accordance with the directions. The information furnished is believed to be accurate to the best of our knowledge. Harita-NTI is not liable for any loss, damage, incidental or consequential. Buyer assumes all responsibility in use, storage and handling of this product.